

Place cabinets near points-of-use to save time by not going to a far away central storage area.

# Sure-Grip® EX Countertop Safety Cabinets

### Use on workbenches for easy access to often-used liquids

Get the fire protection found in larger sized Justrite® safety cabinets in a compact design measuring only 22-in (559-mm) high. Use these cabinets when storing lesser quantities of flammable liquids at a workstation. Portable size keeps work areas flexible. Includes one SpillSlope® safety shelf for storage of multiple small containers. Self-close model with concealed closing mechanism utilizes entire internal space for storage. For more countertop space, choose optional wall hanger assembly for easy mounting on a wall.





Capacity Gal/L	Number of Doors and Style	Dimensions H x W x D		Adj	Approv/Lstg	Yellow	Red	Gray	White	Ship Wt
		Exterior	Interior	Shelves	Regulation	Model No	Model No	Model No	Model No	lb/kg
4/15	countertop; 1 door, manual	22 x 17 x 17 in 559 x 432 x 432 mm	18.5 x 13.75 x 13.75 in 470 x 349 x 349 mm	1	N,O,A	890400	890401	890403	890405	67/30
	countertop; 1 door self-close				N,0,A,I	890420	890421	890423	890425	68/31

#### Extra Accessories

Description	Fits Cabinet Styles	Dimensions W x D	Model No	Ship Wt lb/kg
SpillSlope <sup>®</sup> steel shelf	For 4 gallon (15 L) cabinet	13.375 x 13 in (340 x 330 mm)	29935	4/2
Wall hanger assembly (mounting kit)	4 Gallon (15 L) compac cabinets	—	25951	4/2



## Sure-Grip<sup>®</sup> EX Compac Safety Cabinets

## FM-approved safe storage for up to 15-gallons (57-liters) of flammable liquids

Fully compliant, compact-sized cabinets fit almost anywhere and provide protection even when space is at a premium. Popular 12-gal (45-L) size measures 35-in (889-mm) high to fit under most workbenches. Fire resistant design includes double-walled steel construction with 1-1/2-in (38-mm) of insulating air space and 3-point stainless steel bullet latch for fail-safe, positive door closure. Adjustable SpillSlope® safety shelf directs spills to back and bottom of leakproof 2-in (51-mm) sump. U-Loc™ handle comes with double key set and accepts optional padlock for security. Cabinets also feature dual vents with flame arresters, adjustable leveling feet, and grounding connector to prevent static build-up.

Cabinets meet NFPA and OSHA regulations and are FM-approved. Self-closing models also comply with the International Fire Code.

										<b>D Year</b> nited Warranty
Capacity Gal/L	Number of Doors and Style	Dimensions Exterior	H x W x D Interior	Adj Shelves	Approv/Lstg Regulation	Yellow Model No	Red Model No	Gray Model No	White Model No	Ship Wt lb/kg
12/45	compac; 1 door manual	35 x 23.25 x 18 in	30.5 x 20 x 14.56 in		FM,N,O,A	891200	891201	891203	891205	133/60
12/40	compac; 1 door self-close	889 x 591 x 457 mm	775 x 508 x 370 mm		FM,N,O,A,I	891220	891221	891223	891225	134/61
	compac; 1 door manual	44 x 23.25 x 18 in	39.625 x 20 x 14.56 in	1	FM,N,O,A	891500	891501	891503	891505	154/70
15/57	compac; 1 door self-close	1118 x 591 x 457 mm	1006 x 508 x 370 mm		FM,N,O,A,I	891520	891521	891523	891525	156/71

Extra Accessories				
Description	Fits Cabinet Styles	Dimensions W x D	Model No	Ship Wt lb/kg
SpillSlope <sup>®</sup> steel shelf	12 & 15 gallon (45 L & 57 L) cabinets	19.625 x 14 in (498 x 356 mm)	29936	6/3



