

## REAGENT UPRIGHTS



### slotted post assembly

90" high - RIV0090

- slot pattern suitable for bookend brackets
- adjustable in height on 1" increments
- should be mounted 1/2" on center
- 1" w x 2" d; double-sided, double-slotted post with threaded bolt and nut at top
- adjustable shelving slots begin above the work surface at approximately 16" above bench height
- each post sold with base support

BW

## REAGENT CROSSBARS



### crossbar tube

120" length - RIH0120

- 1" x 2" tube with no penetrations for posts
- field drill holes to locate post bolts
- crossbar comes with 2 plastic end caps
- tube insert for seaming lengths over 120" sold separately

### seam connector insert

insert - RIJ0000

- tube insert for seaming lengths over 120"

BW



### reagent shelving

construction: painted steel  
double-sided, double-slotted post with threaded top-bolt, floor mounting gusset and crossbar

#### installation:

- 1) mount gusset to floor
- 2) adjust post to be plumbed and level
- 3) cut crossbar to length
- 4) drill holes in crossbar for attachment to threaded top-bolts
- 5) secure assembly to base cabinets below
- 6) if possible, secure ends to walls or pipe chases for extra support

color: warm gray

spacing: 27-1/2", 30-1/2", 33-1/2" or 36-1/2" on center for 27", 30", 33" and 36" shelves respectively

shelving: p-lam or phenolic shelving and brackets (see pg. 14)